


技术参数:

- 产品系列: M12 A-code
- 插针数: 4
- 额定电流(40°C): 4A
- 额定电压: 250V
- 额定脉冲电压: 2500V
- 污染等级: 3
- 接触电阻: $\leq 3m\Omega$
- 绝缘电阻: $\geq 100M\Omega$
- 锁紧方式: 螺纹式M12*1
- 电缆类型: PVC, 黑色RAL9005
- 线规: $0.34mm^2$ (AWG22)
- 防护等级: IP67
- 插拔次数: ≥ 100
- 温度范围: $-25^\circ C \dots +85^\circ C$
- 外壳材料: TPU
- 插体材料: PA
- 插针材料: 铜合金
- 插针电镀材料: 金




Technical specification:

- Series: M12 A-Code
- Number of contacts: 4
- Rated current (40°C): 4A
- Rated voltage: 250V
- Rated impulse voltage: 2500V
- Pollution degree: 3
- Contact resistance: $< 3m\Omega$
- Insulation resistance: $\geq 100M\Omega$
- Connector locking system: screw M12*1
- Cable type: PVC, Black RAL 9005
- Wire gauge: $0.34mm^2$ (AWG22)
- Degree of protection: IP67
- Mating cycles: ≥ 100
- Temperature range: $-25^\circ C \dots +85^\circ C$
- Material of housing: TPU
- Material of insert: PA
- Material of contact: copper alloy
- Contact plating: Au


例如型号 "M12-M03A-T-L-PVC-SH",
 "L"表示带线长度, 单位m.

Ex: Part code "M12-M03A-T-L-PVC-SH",
 the "L" represents the cable length, unit m.

针位图 Contact arrangements



接线图 Circuit diagram



					表面处理 Finish	-			图号 Drawing No.	-
					材料 Material	-			产品代号 Part Code	M12-M04A-T-1.5-PVC-SH
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date			产品料号 Part No.	1630044014021
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name
绘图 Drawn	ZQ XU	15.03.2015	标准化 Stand.	-	-	1:1	V2.0	82g	-	-
审核 Checked	ZM LIN	15.03.2015								
工艺 Process	-	-	批准 Approved	YY LUO	15.03.2015	All Dimensions in mm Original Size DIN A 4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		