






技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40°C - $+125^{\circ}\text{C}$
- 防护等级: IP65 (联锁状态, IEC 60529)
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: PG21
- 密封元件: NBR

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40°C - $+125^{\circ}\text{C}$
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: PG21
- Hoods/Housings sealing: NBR



						表面处理 Finish	-	图号 Drawing No.	-
						材料 Material	-	产品代号 Part Code	H32A-SF-4B-PG21
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale	版本 REV.	重量 Weight
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	-	-	-	2:3	V1.0	410g
审核 Checked	P RAO	18.10.2010							-
工艺 Process	-	-	批准 Approved	YY LIN	18.10.2010				
							数量 Qty.	产品名称 Part Name	-
							All Dimensions in mm Original Size DIN A 4		
							WAIN 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		